



# Material Safety Data Sheet

An **RPM** Company

## 24 Hour Emergency Phone Numbers:

### Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

### Transportation/National Response Center:

1-800-535-5053

1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

**IMPORTANT:** Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

## Section 1 - Chemical Product / Company Information

This Material Safety Data Sheet is available in American Spanish upon request.  
Los Datos de Seguridad del Producto pueden obtenerse en Espanol si lo requiere.

<b>Product Name:</b>	Weldwood Nonflammable Contact Cement	<b>Revision Date:</b>	05/06/2014
<b>Product UPC Number:</b>	070798253308, 070798253322, 070798253360	<b>Supersedes:</b>	07/29/2013
<b>Product Use/Class:</b>	Contact Cement	<b>MSDS Number:</b>	00030534001
<b>Manufacturer:</b>	<b>DAP Products Inc.</b> 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non-emergency matters)		

## Section 2 - Hazards Identification

**Emergency Overview:** A white liquid product with a slight odor. **WARNING!** Vapors may be harmful if inhaled. May be harmful or fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. Aspiration may cause pulmonary edema and pneumonitis. Irritating to eyes, respiratory system and skin. May affect the brain or nervous system causing dizziness, headache or nausea. Avoid breathing vapors. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Refer to other MSDS sections for other detailed information.

**Effects Of Overexposure - Eye Contact:** May cause eye irritation. Signs and symptoms may include: pain, tears, swelling, redness and blurred vision.

**Effects Of Overexposure - Skin Contact:** May cause skin irritation. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

**Effects Of Overexposure - Inhalation:** Vapors may be harmful if inhaled. Inhalation of vapors may cause irritation of the nose, throat, lungs and respiratory tract. Inhalation of vapors in high concentration may cause shortness of breath. Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis.

**Effects Of Overexposure - Ingestion:** May be harmful or fatal if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

**Effects Of Overexposure - Chronic Hazards:** Repeated or prolonged exposure may cause skin, respiratory, kidney and liver

damage. Prolonged or repeated inhalation of solvent vapors may cause irregular heartbeat. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure or misuse of toluene can cause liver, kidney, and brain damage as well as cardiac abnormalities.

**Primary Route(s) Of Entry:** Skin Contact, Inhalation

**Medical Conditions which May be Aggravated by Exposure:** Pre-existing eye, skin and pulmonary disorders may be aggravated by exposure to this product.

**Carcinogenicity:**

None

### Section 3 - Composition / Information On Ingredients

Chemical Name	CASRN	Wt%
Carbamide	57-13-6	1-5
Toluene	108-88-3	1-5

### Section 4 - First Aid Measures

**First Aid - Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**First Aid - Skin Contact:** Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing. To remove from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. DO NOT try to peel the solidified material from the skin or use solvents or thinners to dissolve it. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin. Flush exposed area with water while removing contaminated clothing. Get medical attention if irritation persists.

**First Aid - Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

NOTE: Only trained personnel should administer artificial respiration or give oxygen.

**First Aid - Ingestion:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

**Note to Physician:** This material is an aspiration hazard if swallowed. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (may be aggravated by exposure to this material: skin, lungs (for example, asthma-like conditions). Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeat) if exposed to high concentrations of this material.

**COMMENTS:** If over-exposure occurs, call your poison control center at 1-800-222-1222.

### Section 5 - Fire Fighting Measures

**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**Unusual Fire And Explosion Hazards:** None known.

**Special Firefighting Procedures:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

## Section 6 - Accidental Release Measures

**Steps To Be Taken If Material Is Released Or Spilled:** Wear proper protective equipment as specified in Section 8. Immediately eliminate sources of ignition. Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers.

## Section 7 - Handling And Storage

**Handling:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use in well ventilated area. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Avoid breathing vapor and contact with eyes, skin and clothing.

Construction and repair activities can adversely affect indoor air quality. Consult with occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize impact.

**Storage:** Store away from sources of ignition and heat. Keep containers tightly closed. Do not store at temperatures above 120 degrees F. Store containers away from excessive heat and freezing. Store away from caustics and oxidizers.

## Section 8 - Exposure Controls / Personal Protection

Chemical Name	CASRN	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin
Carbamide	57-13-6	NE	NE	NE	NE	NE	NE	No
Toluene	108-88-3	20 PPM	NE	NE	200 PPM	NE	300 PPM	Yes

**Important:** Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

**Note:** An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, coveralls, goggles or other appropriate personal protective equipment, engineering controls or work practices.

**Precautionary Measures:** Please refer to other sections and subsections of this MSDS.

**Engineering Controls:** Use only in well-ventilated areas. Vapors are heavier than air and may spread along floors. Provide sufficient general and/or local exhaust ventilation to maintain exposure below recommended exposure limit.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**Skin Protection:** Solvent-resistant gloves.

**Eye Protection:** Goggles or safety glasses with side shields.

**Other protective equipment:** Provide eyewash and solvent impervious apron if body contact may occur.

**Hygienic Practices:** Remove and wash contaminated clothing before re-use.

## Section 9 - Physical And Chemical Properties

<b>Boiling Range:</b>	Not Established	<b>Vapor Density:</b>	Heavier Than Air
<b>Odor:</b>	Slight	<b>Odor Threshold:</b>	Not Established
<b>Color:</b>	White	<b>Evaporation Rate:</b>	Slower Than n-Butyl Acetate
<b>Solubility in H2O:</b>	Not Established	<b>Specific Gravity:</b>	1.11 - 1.11
<b>Freeze Point:</b>	Not Established	<b>pH:</b>	Not Established
<b>Vapor Pressure:</b>	Not Established	<b>Viscosity:</b>	Not Established
<b>Physical State:</b>	Liquid	<b>Flammability:</b>	Non-Flammable
<b>Flash Point, F:</b>	Greater than 200	<b>Method:</b>	(Seta Closed Cup)

**Lower Explosive Limit, %:** Not Determined**Upper Explosive Limit, %:** Not DeterminedWhen reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Excessive heat and freezing. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.**Incompatibility:** Incompatible with strong bases and oxidizing agents. Avoid contact with strong acids and oxidizable organic materials in the presence of heat.**Hazardous Decomposition Products:** Normal decomposition products, i.e., COx, NOx.**Hazardous Polymerization:** Hazardous polymerization will not occur under normal conditions.**Stability:** Stable under recommended storage conditions.

## Section 11 - Toxicological Information

**Product LD50:** Not Established**Product LC50:** Not Established

CASRN	Chemical Name	LD50	LC50
57-13-6	Carbamide	Rat: 8471 mg/kg	-----
108-88-3	Toluene	-----	Rat: 49 gm/m <sup>3</sup> /4H

**Significant Data with Possible Relevance to Humans:** None.

## Section 12 - Ecological Information

**Ecological Information:** Ecological injuries are not known or expected under normal use.

## Section 13 - Disposal Information

**Disposal Information:** Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a landfill. Do not re-use empty containers.**EPA Waste Code if Discarded (40 CFR Section 261):** None.

## Section 14 - Transportation Information

**DOT Proper Shipping Name:** Not Regulated.**DOT Technical Name:** N.A.**DOT Hazard Class:** N.A.**Packing Group:** N.A.**Hazard Subclass:** N.A.**DOT UN/NA Number:** N.A.

## Section 15 - Regulatory Information

**CERCLA - SARA Hazard Category:**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the

Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard, Chronic Health Hazard

**SARA Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS Number
Toluene	108-88-3

**Toxic Substances Control Act:**

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

**New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product:

Chemical Name	CAS Number
Water	7732-18-5
Polychlorinated Rubber	Proprietary
Rosin ester	Proprietary
Terpene phenolic resin	Proprietary

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%:

Chemical Name	CAS Number
Water	7732-18-5
Polychlorinated Rubber	Proprietary
Rosin ester	Proprietary
Terpene phenolic resin	Proprietary

**California Proposition 65:**

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**Section 16 - Other Information**

**HMIS Ratings:**

Health: 1      Flammability: 2      Reactivity: 0      Personal Protection: X

**Volatile Organic Compounds (VOC), less water less exempts:** g/L: 71      lb/gal: 0.6      wt:wt%: 3.4

**Volatile Organic Compounds (VOC), less water less exempts, less LVP-VOCs:**      wt:wt%: 44.6

**REASON FOR REVISION:** Periodic Update

<b>Legend:</b>	N.A. – Not Applicable	ACGIH – American Conference of Governmental Industrial Hygienists
	N.E. – Not Established	SARA – Superfund Amendments and Reauthorization Act of 1986
	N.D. – Not Determined	NJRTK – New Jersey Right-to-Know Law
	VOC – Volatile Organic Compound	OSHA – Occupational Safety and Health Administration
	PEL – Permissible Exposure Limit	HMIS – Hazardous Materials Identification System
	TLV – Threshold Limit Value	NTP – National Toxicology Program
	CEIL – Ceiling Exposure Limit	STEL – Short Term Exposure Limit
	LD50 – Lethal Dose 50	LC50 – Lethal Concentration 50
	F – Degree Fahrenheit	MSDS – Material Safety Data Sheet
	C – Degree Celsius	CASRN – The Chemical Abstracts Service Registry Number

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. **NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS.** Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.

<End of MSDS>